

## AT125 KOPA ANTI TAMPER IP65 DIFFUSED FLUSH

### MULTI WATT LED (7-18W)

#### General

7/10/13/18W options  
 IP65 rated from below  
 CRI >80 (3000k, 4000k)  
 3 SDCM colour consistency  
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)  
 80 degree diffused optics  
 Easy fit/remove mounting brackets  
 Suitable for use in negative pressure environments  
 IK10 Diffused polycarbonate UV stabilized lens (DP)  
 Security fasteners

#### Driver Details

Non-dimmable:  
 7W = K9W-180 / 10W = K12W-260 /  
 13W = K12W-350 / 18W = K20W-500  
 Trailing edge dimmable (LED dimmer):  
 4W = K4W-100D / 7W = K9W-180D / 10W = K12W-260D /  
 13W = K12W-350D / 18W = K18W-500D

#### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 Silicon seals  
 10 year paint protection



Machined from  
Solid Aluminium

#### Options

CRI >95, COI, Single colours  
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE  
 Bluetooth, 12/24V DC  
 2W auxiliary light (pg 78)  
 Seismic restraint mounting point

#### Size & Weight

Dimension 125mm round, 68mm high  
 Max. Cut-out 115mm round  
 Weight: 500 g

#### Specifications

MODEL	K0718			
TRIM	AT125-Anti Tamper			
OPTICS	80-80° Diffused			
LENS	DP-IK10 Diffused Polycarbonate			
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight	
WATTAGE	7W - 180mA	10W - 260mA	13W - 350mA	18W - 500mA
COLOUR	WH - White	SL - Silver	BL - Black	
IP	IP65 - IP65 Rated			

MODEL - TRIM - OPTICS - COLOUR TEMP - WATTAGE - COLOUR - IP

