

AT125 KOPA ANTI TAMPER IP65 REFLECTOR

MULTI WATT LED (7-18W)

General

7/10/13/18W options
 IP65 rated from below
 CRI >80 (3000k, 4000k)
 3 SDCM colour consistency
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)
 Reflector beam options: 15/25/38/60 degree
 Easy fit /remove mounting brackets
 Suitable for use in negative pressure environments
 IK10 polycarbonate UV stabilized lens
 Security Fasteners

Driver Details

Non-dimmable:
 7W = K9W-180 / 10W = K12W-260 /
 13W = K12W-350 / 18W = K20W-500
 Trailing edge dimmable (LED dimmer):
 4W = K4W-100D / 7W = K9W-180D / 10W = K12W-260D /
 13W = K12W-350D / 18W = K18W-500D

Material & Construction

Solid aluminium with unique copper core heatsink technology
 Silicon seals
 10 year paint protection



Machined from
Solid Aluminium

Options

CRI >95, COI, Single colours
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE
 Bluetooth, 12/24V DC
 20° wall washer lens (WW)
 180° linear spreader lens (LS)
 Seismic restraint mounting point

Size & Weight

Dimension 125mm round, 85mm high
 Max. Cut-out 115mm round
 Weight: 500 g

Specifications

| | | | | |
|------------------|------------------------------|---------------------------|-------------------------|-------------------------|
| MODEL | K0718 | | | |
| TRIM | AT125-Anti Tamper | | | |
| OPTICS | 15-15° Reflector | 25-25° Reflector | 38-38° Reflector | 60-60° Reflector |
| LENS | PC-IK10 Polycarbonate | | | |
| C.C.T | 3K - Warm White | 4K - Neutral White | 5.5K - Daylight | |
| WATTAGE | 7W - 180mA | 10W - 260mA | 13W - 350mA | 18W - 500mA |
| COLOUR | WH - White | SL - Silver | BL - Black | |
| IP RATING | IP65 | | | |

MODEL - **TRIM** - **OPTICS** - **LENS** - **COLOUR TEMP** - **WATTAGE** - **COLOUR** - **IP**

