

## AR160 KOPA ADJUSTABLE ROUND REFLECTOR

MULTI WATT LED (12-35W)

### General

12/16/22/35W options  
 IP44 optical chamber  
 CRI >80 (3000k, 4000k)  
 3 SDCM colour consistency  
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)  
 Reflector beam options: 15/25/38/60 degree  
 Seismic restraint mounting point

### Driver Details

Non-dimmable:  
 12W = K12W-350 / 16W = K20W-500 /  
 22W = K40W-700 / 35W = K40W-1050  
 Trailing edge dimmable (LED dimmer):  
 12W = K12W-350D / 16W = K18W-500D /  
 22W = K36W-700D / 35W = 36W-1050D  
 (100 / 180 / 260mA drivers available)

### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint protection



Machined from  
Solid Aluminium

### Options

CRI >95, COI, Single colours  
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE  
 Bluetooth, 12/24V DC  
 20° wall washer lens (WW)  
 180° linear spreader lens (LS)  
 IK10 polycarbonate UV stabilized lens (PC)  
 Surface Mount Can (pg 46)

### Size & Weight

Dimension: 161mm round, 115mm high  
 Max. Cut-out: 150mm round  
 Weight: 875g

### Specifications

MODEL	K1235			
TRIM	AR160-Adjustable Round			
OPTICS	15-15° Reflector	25-25° Reflector	38-38° Reflector	60-60° Reflector
LENS	CG-Clear Glass			
C.C.T	3K-Warm White	4K-Neutral White	5.5K-Daylight	
WATTAGE	12W-350mA	16W-500mA	22W-700mA	35W-1050mA
COLOUR	WH-White		SL-Silver	BL-Black

MODEL TRIM OPTICS LENS COLOUR TEMP WATTAGE COLOUR

