

AT160 KOPA ANTI TAMPER IP65 DIFFUSED FLUSH

MULTI WATT LED (12-35W)

General

12/16/22/35W options
 IP65 rated from below
 CRI >80 (3000k, 4000k)
 3 SDCM colour consistency
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)
 80 degrees diffused optics
 Pre-mount heavy duty outer trim
 Suitable for use in negative pressure environments
 Security fasteners
 IK10 polycarbonate UV stabilized lens (DP)
 Easy fit /remove mounting brackets
 Seismic restraint mounting point

Driver Details

Non-dimmable:
 12W = K12W-350 / 16W = K20W-500 /
 22W = K40W-700 / 35W = K40W-1050
 Trailing edge dimmable (LED dimmer):
 12W = K12W-350D / 16W = K18W-500D /
 22W = K36W-700D / 35W = 36W-1050D
 (100 / 180 / 260mA drivers available)

Material & Construction

Solid aluminium with unique copper core heatsink technology
 Silicon seals
 10 year paint protection



Machined from
Solid Aluminium

Options

CRI >95, COI, Single colours
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE
 Bluetooth, 12/24V DC
 2W auxiliary light (pg 78)

Size & Weight

Dimension: 160mm round, 98mm high
 Max. Cut-out: 150mm round
 Weight: 1105g

Specifications

MODEL	K1235		
TRIM	AT160-Anti Tamper		
OPTICS	80 - 80° Diffused		
LENS	DP-IK10 Diffused Polycarbonate		
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight
WATTAGE	12W - 350mA	16W - 500mA	22W - 700mA 35W - 1050mA
COLOUR	WH - White	SL - Silver	BL - Black
IP RATING	IP65		

MODEL TRIM OPTICS LENS COLOUR TEMP WATTAGE COLOUR IP

