

## FR140 KOPA FIXED ROUND IP65 DIFFUSED BAFFLE

### MULTI WATT LED (12-35W)

#### General

12/16/22/35W options  
 IP65 rated from below  
 CRI >80 (3000k, 4000k)  
 3 SDCM colour consistency  
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)  
 80 degree diffused optics  
 Seismic restraint mounting point

#### Driver Details

Non-dimmable:  
 12W = K12W-350 / 16W = K20W-500 /  
 22W = K40W-700 / 35W = K40W-1050  
 Trailing edge dimmable (LED dimmer):  
 12W = K12W-350D / 16W = K18W-500D /  
 22W = K36W-700D / 35W = 36W-1050D  
 (100 / 180 / 260mA drivers available)

#### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 Silicon seals  
 10 year paint protection



Machined from  
Solid Aluminium

#### Options

CRI >95, COI, Single colours  
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE  
 Bluetooth, 12/24V DC  
 2W auxiliary light (pg 78)  
 2W emergency light (pg 79)  
 IK10 diffused polycarbonate UV stabilized lens (DP)

#### Size & Weight

Dimension: 140mm round, 98mm high  
 Max. Cut-out: 130mm round  
 Weight: 850g

#### Specifications

MODEL	K1235			
TRIM	FR140-Fixed Round			
OPTICS	80-80° Diffused			
LENS	DA-Diffused Acrylic			
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight	
WATTAGE	12W - 350mA	16W - 500mA	22W - 700mA	35W - 1050mA
COLOUR	WH - White	SL - Silver	BL - Black	
IP RATING	IP65			

MODEL - TRIM - OPTICS - COLOUR TEMP - WATTAGE - COLOUR - IP

