

FR170 KOPA FIXED ROUND IP65 DIFFUSED

MULTI WATT LED (48-60W)

General

48/60W options
 IP65 rated from below
 CRI >80 (3000k, 4000k)
 3 SDCM colour consistency
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)
 80 degrees diffused optics
 Pre-mount heavy duty outer trim
 Suitable for use in negative pressure environments
 Easy fit/remove mounting brackets
 IK10 Diffused polycarbonate UV stabilized lens
 Seismic restraint mounting point

Driver Details

Standard driver: non-dimmable
 (K60W-1400 / K70W-1750)
 (100 / 180 / 260 / 350 / 500 / 700 / 1050mA drivers available)

Material & Construction

Solid aluminium with unique copper core heatsink technology
 Silicon seals
 10 year paint protection



Machined from
Solid Aluminium

Options

CRI >95, COI, Single colours
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM
 Anti tamper fasteners

Size & Weight

Dimension: 170mm round, 180mm high
 Max. Cut-out: 150mm round
 Weight: 1820g

Specifications

MODEL	K4860		
TRIM	FR170 - Fixed Round		
OPTICS	80 - 80° Diffused		
LENS	DP-Diffused Polycarbonate		
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight
WATTAGE	48W - 1400mA	60W - 1750mA	
COLOUR	WH - White	SL - Silver	BL - Black
IP RATING	IP65		

MODEL TRIM OPTICS LENS COLOUR TEMP WATTAGE COLOUR IP

