


Specifications



-  5650K ~ 6000K
-  3800K ~ 4100K
-  2800K ~ 3050K
-  2800K ~ 6000K

New!

5W A55




Power Consumption	5W
Field Angle	Wide angle
Color Temperature	CW / WW
CRI	≥ 70
Finish	Silver
Surface Temperature	60 °C
Weight	150 ± 5 g






New!


7W PAR20












Power Consumption	7W
Field Angle	25° / 40° / 60°
Color Temperature	CW / WW
CRI	≥ 70
Finish	Silver
Surface Temperature	60 °C
Weight	215 ± 5 g




10W PAR30






Power Consumption	10W
Field Angle	25° / 40° / 60° / 140°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	White
Surface Temperature	55 °C
Weight	215 ± 5 g



10W PAR30L




Power Consumption	10W
Field Angle	25° / 40° / 60° / 140°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	White
Surface Temperature	55 °C
Weight	280 ± 5 g





New!


10W PAR30P



Power Consumption	10W
Field Angle	25° / 40° / 60° / 140°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	White
Surface Temperature	55 °C
Weight	230 ± 5 g



15W PAR38



Power Consumption	15W
Field Angle	30° / 60°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	White
Surface Temperature	60 °C
Weight	400 ± 5 g

