











**New!**

## 3W MR16




Power Consumption	3W
Field Angle	15° / 38° / 60°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	White / Silver
Surface Temperature	55 °C
Weight	40 ± 5 g

○ 5650K ~ 6000K    ● 3800K ~ 4100K    ● 2800K ~ 3050K









**New!**


## 3W GU10



Power Consumption	3W
Field Angle	15° / 38° / 60°
Color Temperature	CW / WW
CRI	≥ 70
Finish	White / Silver
Surface Temperature	60 °C
Weight	50 ± 5 g




## 5W MR16









Power Consumption	5W
Field Angle	10° / 38°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	Gray
Surface Temperature	65 °C
Weight	60 ± 5 g


## 5W GU10



Power Consumption	5W
Field Angle	10° / 38°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	Silver
Surface Temperature	65 °C
Weight	115 ± 5 g



## 5W PAR16



Power Consumption	5W
Field Angle	10° / 38°
Color Temperature	CW / NW / WW
CRI	≥ 70
Finish	Silver
Surface Temperature	65 °C
Weight	120 ± 5 g

