



ARCHITECTURAL

# KOPA ARCHITECTURAL CONTENTS



**PAGE 1**  
KASS0412  
KOPA SURFACE SPOT



**PAGE 2**  
KASD0412  
KOPA SURFACE DOWNLIGHT



**PAGE 3**  
KASRS0412  
KOPA SEMI RECESSED SPOTLIGHT



**PAGE 4**  
KA0412-FR88  
KOPA FIXED DOWNLIGHT



**PAGE 5**  
KATS0412  
KOPA TRACK SPOT

## KASS0412 KOPA SURFACE SPOTLIGHT

4-12 WATT LED

### General

CRI>95+ (3000k, 4000k)  
 3 SDCM colour consistency  
 IP44 optical chamber  
 L70 50,000 hours  
 Surface mount base  
 Low glare interchangeable magnetic baffle

### Driver Details

Non Dim remote driver  
 (110mA = 4W / 180mA = 7W / 260mA = 10W / 300mA = 12W)  
 Remote driver version available

### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint treatment



Machined from  
 Solid Aluminium

### Options

COI, Single colours, Remote Drivers;  
 Trailing edge dim, DALI Dim, CASAMBI wireless dim.  
 Honeycomb internal baffle  
 Diffusing lens

### Size & Weight

Dimension: 65mm diameter x ~235mm in height, 88mm base  
 Weight:700g

### Specifications

MODEL	KASS0412		
OPTICS	25-25° Reflector	38-38° Reflector	50-50° Reflector
	80-80° Diffused with low profile baffle		
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight
WATTAGE	4W - 110mA		12W - 300mA
COLOUR	WH - White	SL - Silver	BL - Black

MODEL OPTICS COLOUR TEMP WATTAGE COLOUR



## KASD0412 KOPA SURFACE DOWNLIGHT

4-12 WATT LED

### General

CRI>95+ (3000k, 4000k)  
 3 SDCM colour consistency  
 IP44 optical chamber  
 L70 50,000 hours  
 Surface mount base  
 Low glare interchangeable magnetic baffle

### Driver Details

Non Dim Intengral  
 (110mA = 4W / 180mA = 7W / 260mA = 10W / 300mA = 12W)  
 Remote driver version available

### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint treatment



Machined from  
 Solid Aluminium

### Options

COI, Single colours, Remote Drivers;  
 Trailing edge dim, DALI Dim, CASAMBI wireless dim.  
 Honeycomb internal baffle  
 Diffusing lens

### Size & Weight

Dimension: 65mm diameter x ~228mm in height, 88mm base  
 Weight:700g

### Specifications

MODEL	KASD0412		
OPTICS	25-25° Reflector	38-38° Reflector	50-50° Reflector
	80-80° Diffused with low profile baffle		
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight
WATTAGE	4W - 110mA		12W - 300mA
COLOUR	WH - White	SL - Silver	BL - Black

MODEL OPTICS COLOUR TEMP WATTAGE COLOUR



## KASRS0412 KOPA SEMI RECESSED SPOTLIGHT

4-12 WATT LED

### General

CRI>95+ (3000k, 4000k)  
 3 SDCM colour consistency  
 IP44 optical chamber  
 L70 50,000 hours  
 Semi recessed base  
 Low glare interchangeable magnetic baffle

### Driver Details

Non Dim remote driver  
 (110mA = 4W / 180mA = 7W / 260mA = 10W / 300mA = 12W)  
 Remote driver version available

### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint treatment



Machined from  
 Solid Aluminium

### Options

COI, Single colours, Remote Drivers;  
 Trailing edge dim, DALI Dim, CASAMBI wireless dim.  
 Honeycomb internal baffle  
 Diffusing lens

### Size & Weight

Dimension: 88mm diameter recessing trim x ~220mm in height, 88mm base  
 Weight:700g

### Specifications

MODEL	KASRS0412		
OPTICS	25-25° Reflector	38-38° Reflector	50-50° Reflector
	80-80° Diffused with low profile baffle		
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight
WATTAGE	4W - 110mA		12W - 300mA
COLOUR	WH - White	SL - Silver	BL - Black

MODEL OPTICS COLOUR TEMP WATTAGE COLOUR



## KA0412-FR88 KOPA FIXED DOWNLIGHT

4-12 WATT LED

### General

CRI>95+ (3000k, 4000k)  
 3 SDCM colour consistency  
 IP44 optical chamber  
 L70 50,000 hours  
 Clamp recess bracket  
 Low glare interchangeable magnetic baffle

### Driver Details

Non Dim remote driver  
 (110mA = 4W / 180mA = 7W / 260mA = 10W / 300mA = 12W)  
 Remote driver version available

### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint treatment



Machined from  
 Solid Aluminium

### Options

COI, Single colours, Remote Drivers;  
 Trailing edge dim, DALI Dim, CASAMBI wireless dim.  
 Honeycomb internal baffle  
 Diffusing lens

### Size & Weight

Dimension: 88mm diameter x ~105mm in height  
 Weight:700g

### Specifications

MODEL	KA0412-F288		
OPTICS	25-25° Reflector	38-38° Reflector	50-50° Reflector
	80-80° Diffused with low profile baffle		
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight
WATTAGE	4W - 110mA		12W - 300mA
COLOUR	WH - White	SL - Silver	BL - Black

MODEL OPTICS COLOUR TEMP WATTAGE COLOUR



## KATS0412 KOPA TRACKSPOT

### 12 WATT LED

#### General

CRI>95+ (3000k, 4000k)  
 3 SDCM colour consistency  
 IP44 optical chamber  
 L70 50,000 hours  
 3 circuit track adaptor (standard)  
 Low glare black baffle

#### Driver Details

Non Dim remote driver (track mount integral)

#### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint treatment



Machined from  
 Solid Aluminium

#### Options

DALI version\*  
 Wireless systems on application\*

#### Size & Weight

Dimension: 65mm diameter x 150-120mm in height  
 Weight:820g

#### Specifications

MODEL	KATS0412		
OPTICS	25-25° Reflector	38-38° Reflector	50-50° Reflector
	80-80° Diffused with low profile baffle		
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight
WATTAGE	4W - 110mA		12W - 300mA
COLOUR	WH - White	SL - Silver	BL - Black

MODEL OPTICS COLOUR TEMP WATTAGE COLOUR



# LED PERFORMANCE AT ITS VERY BEST.



[SALES@KOPAGLOBAL.COM](mailto:SALES@KOPAGLOBAL.COM)  
[WWW.KOPAGLOBAL.COM](http://WWW.KOPAGLOBAL.COM)

Copyright© 2015 Kopa Global Pty Ltd, All Rights Reserved  
All information provided is subject to change without notice.