

MILLIAMPER TO WATTAGE CONVERSION TABLE

| mA | K3/KBL/ KBL-S | K0718 | K1235 | K4860 | KSL | COLOUR TUNEABLE (DT8 DRIVER MUST BE USED) |
|-----------|--------------------------|--------------|--------------|--------------|-------------------------|--|
| 100mA | | 4W | | | | |
| 180mA | | 7W | | | | |
| 250mA | | 10W | | | | 12W |
| 300mA | | | | | | 14W |
| 350mA | 1W | 13W | 12W | | 7W | 16W |
| 400mA | | | | | | 23W |
| 500mA | | 18W | 16W | | 21W or 42W (2x drivers) | |
| 550mA | | | | | | 26W |
| 600mA | | | | | | 28W |
| 650mA | | | | | | 30W |
| 700mA | 3W | | 22W | | 30W | 33W |
| 1050mA | | | 35W | | | |
| 1400mA | | | | 48W | | |
| 1750mA | | | | 60W | | |

DRIVERS CONSTANT CURRENT

| NON DIM | | LENGTH (mm) | WIDTH (mm) | HEIGHT (mm) | |
|---|---|-------------|------------|-------------|--------|
| K4W-100 | 3-4W 100mA NON-DIM DRIVER , fitted with 2 pin 1.2m F&P + Kopa lead (25-40V) | 97 | 37 | 24 | 100mA |
| K4W-350 | 1-12W 350mA NON-DIM DRIVER , fitted with 2 pin 1.2m F&P + Kopa lead FOR USE WITH THE K3-AR52/KBL & KBL-S | 115 | 40 | 22 | 350mA |
| K9W-180 | 9W 350mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 97 | 37 | 24 | 180mA |
| K12W-250 | 12W 250mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 97 | 37 | 24 | 250mA |
| K12W-350 | 12W 350mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 97 | 37 | 24 | 350mA |
| K20W-500 | 20W 500mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 115 | 41 | 28 | 500mA |
| K40W-700 | 40W 700mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 115 | 41 | 28 | 700mA |
| K40W-1050 | 40W 1050mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 115 | 41 | 28 | 1050mA |
| K60W-1400 | 60W 1400mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 183 | 60 | 33 | 1400mA |
| LC165/1750mA TEC SR | 65W 1750mA NON-DIM DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 158 | 82 | 34 | 1750mA |
| TRAILING EDGE | | LENGTH (mm) | WIDTH (mm) | HEIGHT (mm) | |
| K9W-180D | 9W 180mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 98 | 46 | 31 | 180mA |
| K12W-250D | 12W 250mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 98 | 46 | 31 | 250mA |
| K12W-300D | 12W 300mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 113 | 45 | 28 | 300mA |
| K12W-350D | 12W 350mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 98 | 46 | 31 | 350mA |
| K18W-350D | 18W 350mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead FOR USE WITH THE KSL | 113 | 45 | 28 | 350mA |
| K18W-500D | 18W 500mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 117 | 46 | 31 | 500mA |
| K30W-500D | 30W 500mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead FOR USE WITH THE KSL | 142 | 50 | 25 | 500mA |
| K36W-700D | 36W 700mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 117 | 46 | 31 | 700mA |
| K36W-1050D | 36W 1050mA TRAILING EDGE DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | 165 | 53 | 25 | 1050mA |
| DALI DIM - FOR USE WITH K4860 ONLY | | LENGTH (mm) | WIDTH (mm) | HEIGHT (mm) | |
| LCA60/1750mA-ONE4ALL-SR-F&P-KL | DALI / DSI / PUSH DIM , 1750mA, fitted with 3 pin 1.2m F&P + Kopa Lead | 220 | 85 | 32 | 1750mA |

DRIVERS CONSTANT CURRENT

DALI2/PUSH DIM/BI LEVEL - FLICKER FREE DRIVERS

| | | | |
|------------------------------|--|---|--------|
| TCI-127508-20W-125FP | DALI 2, PUSH DIM & BILEVEL 20W, 125mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 10-54V, 2 pin 1.2m F&P + Kopa lead (TCI 7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10474/professionale-in-dali-20/ | 125mA |
| TCI-127508-20W-150FP | DALI 2, PUSH DIM & BILEVEL 20W, 150mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 10-54V, 2 pin 1.2m F&P + Kopa lead (TCI 7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10474/professionale-in-dali-20/ | 150mA |
| TCI-127508-20W-250FP | DALI 2, PUSH DIM & BILEVEL 20W, 250mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 10-54V, 2 pin 1.2m F&P + Kopa lead (TCI 7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10474/professionale-in-dali-20/ | 250mA |
| TCI-127481-40W-300FP | DALI 2, PUSH DIM & BILEVEL 40W, 300mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 15-44V, 2 pin 1.2m F&P + Kopa lead (7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10479/professionale-in-dali-40/ | 300mA |
| TCI-127481-40W-350FP | DALI 2, PUSH DIM & BILEVEL 40W, 350mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 15-44V, 2 pin 1.2m F&P + Kopa lead (7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10479/professionale-in-dali-40/ | 350mA |
| TCI-127481-40W-500FP | DALI 2, PUSH DIM & BILEVEL 40W, 500mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 10-44V, 2 pin 1.2m F&P + Kopa lead (7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10479/professionale-in-dali-40/ | 500mA |
| TCI-127481-40W-700FP | DALI 2, PUSH DIM & BILEVEL 40W, 700mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 7-43V, 2 pin 1.2m F&P + Kopa lead (7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10479/professionale-in-dali-40/ | 700mA |
| TCI-127481-40W-1050FP | DALI 2, PUSH DIM & BILEVEL 40W, 1050mA, FLICKER FREE, DIM TO WARM - AMPLITUDE, 5-38V, 2 pin 1.2m F&P + Kopa lead (7/10 year warranty) - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/10479/professionale-in-dali-40/ | 1050mA |

CASAMBI WIRELESS DIM DRIVERS - REQUIRES CASAMBI ECOSYSTEM TO CONTROL (free IOS/Android app available <https://www.casambi.com/products.html>)

| | | | |
|---------------------------------------|--|---|--------|
| LCA10/150mA-CWD-SR-F&P-KL | CASAMBI WIRELESS DIM, 150mA, fitted with 3 pin 1.2m F&P + Kopa lead | https://www.tridonic.com/en/int/product/29016?tab=0 | 150mA |
| LCA10/200mA-CWD-SR-F&P-KL | CASAMBI WIRELESS DIM, 200mA, fitted with 3 pin 1.2m F&P + Kopa lead | https://www.tridonic.com/en/int/product/29016?tab=0 | 200mA |
| LCA10/250mA-CWD-SR-F&P-KL | CASAMBI WIRELESS DIM, 250mA, fitted with 3 pin 1.2m F&P + Kopa lead | https://www.tridonic.com/en/int/product/29016?tab=0 | 250mA |
| LCA17/350mA-CWD-SR-F&P-KL | CASAMBI WIRELESS DIM, 350mA, fitted with 3 pin 1.2m F&P + Kopa lead | https://www.tridonic.com/en/int/product/29017?tab=0 | 350mA |
| LCA25/500mA-CWD-SR-F&P-KL | CASAMBI WIRELESS DIM, 500mA, fitted with 3 pin 1.2m F&P + Kopa lead | https://www.tridonic.com/en/int/product/29018?tab=0 | 500mA |
| LCA25/700mA-CWD-SR-F&P-KL | CASAMBI WIRELESS DIM, 700mA, fitted with 3 pin 1.2m F&P + Kopa lead | https://www.tridonic.com/en/int/product/29018?tab=0 | 700mA |
| LCA45/1050mA-CWD-SR-F&P-KL | CASAMBI WIRELESS DIM, 1050mA, fitted with 3 pin 1.2m F&P + Kopa lead | https://www.tridonic.com/en/int/product/29039?tab=0 | 1050mA |

DALI, 1-10V & PUSH DIM

| | | | |
|--------------------------|---|---|--------|
| TCI-127413-350FP | DALI,1-10V & PUSH DIM, 50W Max, 350mA, fitted with 2 pin 1.2m F&P + Kopa lead - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/4989/dc-maxi-jolly-us-dali/ | 350mA |
| TCI-127413-500FP | DALI,1-10V & PUSH DIM, 50W Max, 500mA, fitted with 2 pin 1.2m F&P + Kopa lead - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/4989/dc-maxi-jolly-us-dali/ | 500mA |
| TCI-127413-700FP | DALI,1-10V & PUSH DIM, 50W Max, 700mA, fitted with 2 pin 1.2m F&P + Kopa lead - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/4989/dc-maxi-jolly-us-dali/ | 700mA |
| TCI-127413-1050FP | DALI,1-10V & PUSH DIM, 50W Max, 1050mA, fitted with 2 pin 1.2m F&P + Kopa lead - Drivers set to 350mA / onsite dip switch setting required before use | https://www.tci.it/prodotti/alimentatori-led/4989/dc-maxi-jolly-us-dali/ | 1050mA |

1-10V DIM DRIVER (ONLY FOR USE WITH K3-AR52/KBL/KBL-S)

| | | | |
|----------------------|--|--|-------|
| K8W-350 1-10V | 8W 350mA 1-10V DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | | 350mA |
| K8W-700 1-10V | 8W 500mA 1-10V DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | | 700mA |

DALI (ONLY FOR USE WITH K3-AR52/KBL/KBL-S)

| | | | |
|---------------------|---|--|-------|
| K8W-350-DALI | 8W 350mA DALI DIMMABLE DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | | 350mA |
|---------------------|---|--|-------|

DALI DT8 DRIVER (ONLY FOR USE WITH COLOUR TUNEABLE FITTINGS)

| | | | |
|-----------------|--|---|-----------|
| K20W-DT8 | 20W 250-450mA (DIP SWITCH) DALI DT8 DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | https://www.lpegroup.com.au/assets/PDF/DRIVERS/KOPAGLOBAL/K20W-DT8.pdf | 250-450mA |
| K40W-DT8 | 40W 550-700mA (DIP SWITCH) DALI DT8 DRIVER, fitted with 2 pin 1.2m F&P + Kopa lead | https://www.lpegroup.com.au/assets/PDF/DRIVERS/KOPAGLOBAL/K40W-DT8.pdf | 550-700mA |