

AR110 KOPA ADJUSTABLE ROUND DIFFUSED BAFFLE

MULTI WATT LED (7-18W)

General

7/10/13/18W options
 IP44 optical chamber
 CRI >80 (3000k, 4000k)
 3 SDCM colour consistency
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)
 80 degree diffused optics

Driver Details

Non-dimmable:
 7W = K9V-180 / 10W = K12W-260 /
 13W = K12W-350 / 18W = K20W-500
 Trailing edge dimmable (LED dimmer):
 4W = K4W-100D / 7W = K9V-180D / 10W = K12W-260D
 13W = K12W-350D / 18W = K18W-500D

Material & Construction

Solid aluminium with unique copper core heatsink technology
 10 year paint protection



Machined from
Solid Aluminium

Options

CRI>95, COI, Single colours
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE
 Bluetooth, 12/24V DC
 2W auxiliary light (pg 78)
 IK10 polycarbonate UV stabilized lens (DP)
 Seismic restraint mounting point

Size & Weight

Dimension: 110mm round, 80mm high
 Max. Cut-out: 100mm round
 Weight: 370g

Specifications

MODEL	K0718			
TRIM	AR110-Adjustable Round			
OPTICS	80-80° Diffused			
LENS	DA-Diffused Acrylic			
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight	
WATTAGE	7W -180mA	10W -260mA	13W -350mA	18W -500mA
COLOUR	WH -White	SL -Silver	BL -Black	

MODEL - **TRIM** - **OPTICS** - **COLOUR TEMP** - **WATTAGE** - **COLOUR**

