

## FR130 KOPA FIXED ROUND IP65 REFLECTOR

### MULTI WATT LED (7-18W)

#### General

7/10/13/18W options  
 IP65 rated from below  
 CRI >80 (3000k, 4000k)  
 3 SDCM colour consistency  
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)  
 Reflector beam options: 15/25/38/60 degree

#### Driver Details

Non-dimmable:  
 7W = K9V-180 / 10W = K12W-260 /  
 13W = K12W-350 / 18W = K20W-500  
 Trailing edge dimmable (LED dimmer):  
 4W = K4W-100D / 7W = K9V-180D / 10W = K12W-260D  
 13W = K12W-350D / 18W = K18W-500D

#### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint protection



Machined from  
Solid Aluminium

#### Options

CRI>95, COI, Single colours  
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE  
 Bluetooth, 12/24V DC  
 IK10 polycarbonate UV stabilized lens (PC)  
 Seismic restraint mounting point

#### Size & Weight

Dimension: 130mm round, 102mm high  
 Max. Cut-out: 120mm round  
 Weight: 490g

#### Specifications

<b>MODEL</b>	<b>K0718</b>			
<b>TRIM</b>	<b>FR130-Fixed Round</b>			
<b>LENS</b>	<b>CG-Clear Glass</b>			
<b>OPTICS</b>	<b>15-15° Reflector</b>	<b>25-25° Reflector</b>	<b>38-38° Reflector</b>	<b>60-60° Reflector</b>
<b>C.C.T</b>	<b>3K - Warm White</b>	<b>4K - Neutral White</b>	<b>5.5K - Daylight</b>	
<b>WATTAGE</b>	<b>7W - 180mA</b>	<b>10W - 260mA</b>	<b>13W - 350mA</b>	<b>18W - 500mA</b>
<b>COLOUR</b>	<b>WH - White</b>	<b>SL - Silver</b>	<b>BL - Black</b>	
<b>IP RATING</b>	<b>IP65</b>			

**MODEL** **TRIM** **OPTICS** **LENS** **COLOUR TEMP** **WATTAGE** **COLOUR** **IP**

