

## FR140TL KOPA TRIMLESS DIFFUSED

MULTI WATT LED (7-18W)

### General

7/10/13/18W options  
 Screwless, magnetic cover  
 CRI>80 (3000k, 4000k)  
 3 SDCM colour consistency  
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)  
 80 degree diffused optics  
 Easy fit lock down brackets

### Driver Details

Non-dimmable:  
 7W = K9V-180 / 10W = K12W-260 /  
 13W = K12W-350 / 18W = K20W-500  
 Trailing edge dimmable (LED dimmer):  
 4W = K4W-100D / 7W = K9V-180D / 10W = K12W-260D /  
 13W = K12W-350D / 18W = K18W-500D

### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 Steel trimless housing  
 Silicon seals  
 10 year paint protection



Machined from  
Solid Aluminium

### Options

CRI>95, COI, Single colours  
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE  
 Bluetooth, 12/24V DC  
 2W auxiliary light (pg 78)  
 IK10 diffused polycarbonate UV stabilized lens (DP)  
 Seismic restraint mounting point

### Size & Weight

Dimensions: 140mm round, perforated plaster flange 22mm width,  
 122mm height  
 Max. Cut-out: 145mm round  
 Weight: 1850g

### Specifications

MODEL	K0718			
TRIM	FR140TL			
OPTICS	80 - 80° Diffused			
LENS	DA-Diffused Acrylic			
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight	
WATTAGE	7W-180mA	10W-260mA	13W-350mA	18W-500mA
COLOUR	WH - White	SL - Silver	BL - Black	Custom Colours
IP RATING	IP65			

MODEL - TRIM - OPTICS - COLOUR TEMP - WATTAGE - COLOUR - IP

