

FR140TL KOPA TRIMLESS REFLECTOR

MULTI WATT LED (7-18W)

General

7/10/13/18W options
 Screwless, magnetic reflector cover
 CRI>80 (3000k, 4000k)
 3 SDCM colour consistency
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)
 Reflector beam options: 15/25/38/60 degree
 Easy fit lock down brackets

Driver Details

Non-dimmable:
 7W = K9V-180 / 10W = K12W-260 /
 13W = K12W-350 / 18W = K20W-500
 Trailing edge dimmable (LED dimmer):
 4W = K4W-100D / 7W = K9V-180D / 10W = K12W-260D/
 13W = K12W-350D / 18W = K18W-500D

Material & Construction

Solid aluminium with unique copper core heatsink technology
 Steel trimless housing
 Silicon seals
 10 year paint protection



Machined from
Solid Aluminium

Options

CRI>95, COI, Single colours
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE
 Bluetooth, 12/24V DC
 IK10 polycarbonate UV stabilized lens (PC)
 Seismic restraint mounting point

Size & Weight

Dimensions: 140mm round, perforated plaster flange 22mm width,
 145mm height
 Max. Cut-out: 145mm round
 Weight: 1850g

Specifications

MODEL	K0718			
TRIM	FR140TL			
OPTICS	15-15° Reflector	25-25° Reflector	38-38° Reflector	60-60° Reflector
LENS	CG-Clear Glass			
C.C.T	3K - Warm White	4K - Neutral White	5.5K - Daylight	
WATTAGE	7W-180mA	10W-260mA	13W-350mA	18W-500mA
COLOUR	WH-White	BL-Black	SL-Silver	Custom Colours
IP RATING	IP65			

MODEL TRIM OPTICS LENS COLOUR TEMP WATTAGE COLOUR IP

