

## FS100 KOPA FIXED SQUARE DIFFUSED BAFFLE

MULTI WATT LED (7-18W)

### General

7/10/13/18W options  
 IP44 optical chamber  
 CRI >80 (3000k, 4000k)  
 3 SDCM colour consistency  
 L70 (9K), B10 > 50,000 hours (tested at max.wattage)  
 80 degree diffused optics

### Driver Details

Non-dimmable:  
 7W = K9W-180 / 10W = K12W-260 /  
 13W = K12W-350 / 18W = K20W-500  
 Trailing edge dimmable (LED dimmer):  
 4W = K4W-100D / 7W = K9W-180D / 10W = K12W-260D /  
 13W = K12W-350D / 18W = K18W-500D

### Material & Construction

Solid aluminium with unique copper core heatsink technology  
 10 year paint protection



Machined from  
Solid Aluminium

### Options

CRI>95, COI, Single colours  
 Dimmable driver 1-10V, DALI, DSI, PUSH DIM, ZIGBEE  
 Bluetooth, 12/24V DC  
 2W auxiliary light (pg 78)  
 2W emergency light (pg 79)  
 IK10 polycarbonate UV stabilized lens (DP)  
 Seismic restraint mounting point

### Size & Weight

Dimension: 100mm square, 75mm high  
 Max. Cut-out: 90mm round  
 Weight: 335g

### Specifications

<b>MODEL</b>	<b>K0718</b>		
<b>TRIM</b>	<b>FS100-Fixed Square</b>		
<b>OPTICS</b>	<b>80-80° Diffused</b>		
<b>LENS</b>	<b>DA-Diffused Acrylic</b>		
<b>C.C.T</b>	<b>3K</b> - Warm White	<b>4K</b> - Neutral White	<b>5.5K</b> - Daylight
<b>WATTAGE</b>	<b>7W</b> - 180mA	<b>10W</b> - 260mA	<b>13W</b> - 350mA
<b>COLOUR</b>	<b>WH</b> - White	<b>SL</b> - Silver	<b>BL</b> - Black

**MODEL** | **TRIM** | **OPTICS** | **COLOUR TEMP** | **WATTAGE** | **COLOUR**

