

## VL26A

- 26mm wide x 24mm high
- Angled diffuser
- Remote Driver
- Standard finish White/Black (other colours optional)
- 7 watts/m or 14 watts/m
- Solid PCB
- 3K, 4k CRI80+ (CRI95+ optional)
- Reported L70 B10 (10K) > 60,000 hrs
- Forecasted L70 83,000 hrs
- Ledvision PMMA high impact diffuser
- Pre-mount clips included
- RGBW/Mono colours optional
- Manufactured in module lengths up to 4m
- Can be installed continuous
- Rear or End feed entry available
- All photometric data provided in absolute lumens
- Manufactured in South Australia





# VL26A

	VOLTAGE	WATTAGE
<b>VL26A-7</b>	DC24V	7W/m
<b>VL26A14</b>	DC24V	14W/m
<b>VL26A-RGB*</b>	DC24V	14.4W/m
<b>VL26A-RGBW*</b>	DC24V	14.4W/m

\* Flexible Strip Used

## VL26A - Angled Diffuser (36w x 24h)

VL26A - 3000/4000K (7w per metre)



VL26A - 3000/4000K (14w per metre)



VL26A - RGB (14.4w per metre)




VL26A - RGBW (14.4w per metre)



## VL26A PROFILE:

26mm wide x 24mm high



### INCLUSIONS :

Solid PCB (7 & 14W, 3K, 4K)

### DIFFUSER :

Ledvision PMMA  
high impact

### OPTIONS \*on request :

Custom Colours