

VL26R

- 36mm wide x 22mm high
- Recessed Mounting
- Remote Driver
- Standard finish White/Black (other colours optional)
- 7 watts/m or 14 watts/m
- Solid PCB
- 3K, 4k CRI80+ (CRI95+ optional)
- Reported L70 B10 (10K) > 60,000 hrs
- Forecasted L70 83,000 hrs
- Ledvision PMMA high impact diffuser
- Spring Recessed Brackets included
- RGBW/Mono Colours optional
- Manufactured in module lengths up to 4m
- Can be installed continuous
- Rear power entry
- All photometric data provided in absolute lumens
- Manufactured in South Australia





VL26R

	VOLTAGE	WATTAGE
VL26R-7	DC24V	7W/m
VL26R14	DC24V	14W/m
VL26R-RGB*	DC24V	14.4W/m
VL26R-RGBW*	DC24V	14.4W/m

* Flexible Strip Used

VL26R - RECESSED (36w x 22h)

VL26R - 3000/4000K (7w per metre)



VL26R - 3000/4000K (14w per metre)



VL26R - RGB (14.4w per metre)




VL26R - RGBW (14.4w per metre)



VL26R PROFILE:

36mm wide x 22mm high



INCLUSIONS :

Solid PCB (7 & 14W, 3K, 4K)

DIFFUSER :

Ledvision PMMA
high impact

OPTIONS *on request :

Custom Colours