

VL70R

- 87 wide x 75 high
- Integral driver
- Downlight options available to 4/7/10/13W
- Emergency Option available
- Integral tensioning joiner
- Plug and play wiring system
- Integral mounting guides (easy install)
- Standard Colour White or Black (other colours optional)
- 12 watts/m, 17 watts/m, 24 watts/m, 32 watts/m or 38 watts/m
- Solid PCB (removable and replaceable)
- Mitred and Cross Over bends available (90 and 135 degree standard)
- 3K, 4k CRI80+ (CRI95+ optional)
- Reported L70 B10 (10K) > 60,000 hrs
- Forecasted L70 83,000 hrs
- Ledvision PMMA high impact diffuser
- RGBW optional
- Manufactured in module lengths up to 4m
- Rear Power Entry
- All photometric data provided in absolute lumens
- Manufactured in South Australia



VL70R

	VOLTAGE	WATTAGE
VL70-12	240V AC	12W/m
VL70-17	240V AC	17W/m
VL70-24	240V AC	24W/m
VL70-32	240V AC	32W/m
VL70-38	240V AC	38W/m
VL70-RGBW*	240V AC	28.8W/m

Downlight options available to 4/7/10/13W.

* Flexible Strip Used

VL70 - SURFACE / SUSPENDED

VL70-12 - 3000/4000K (12w per metre)



VL70-17 - 3000/4000K (17w per metre)



VL70-24 - 3000/4000K (24w per metre)



VL70-32 - 3000/4000K (32w per metre)



VL70-38 - 3000/4000K (38w per metre)




VL70-28.8 - Dual RGBW (28.8w per metre)



VL70 R PROFILE:

87mm wide x 75 mm high

75mm



INCLUSIONS :
Solid PCB

DIFFUSER :
Ledvision PMMA
high impact

87mm

OPTIONS :
Custom colours
Downlights
Emergency